

KLEEMANN Escalators & Moving Walks

- Their functional design, in combination with the multiple choices of dimensions and equipment, offer an exceptional attractive image that fits absolutely with the ambience
- Absolute implementation at airports, undergrounds, malls, hotels, offices, etc
- Cover any safety requirements, having a high performance
- Long duration and operation life
- Noiseless operation and transport quality
- CE marking and complete certification according to EN 115 standard
- Easy installation and maintenance
- Technical support and guarantee by KLEEMANN



ESCALATORS	il fall		
ТҮРЕ	KEC COMMERCIAL	KEH HEAVY DUTY	
Working hours per day	16-20 hours	20-24 hours	
Capacity *	Up to 11700 passengers / hour		
Inclination	30°/35°		
Pallet width [mm]	600 / 800 / 1000		
Balustrade design	Vertical safety glass (10 mm safety tempered glass). Height 1000 mm	Vertical safety glass (10 mm safety tempered glass) / Inclined satine 2mm. Height 1000 mm	
Operating Speed [m/sec]	0.5	0.5-0.65	
Vertical rise [m]	2-7.5	2-25	
Motor type	One speed or VVVF		
Installation	Indoor, Semi-outdoor **, Outdoor		

MOVING WALKS				
ТҮРЕ	KTC COMMERCIAL	KTH HEAVY DUTY	KTW HEAVY DUTY	
Working hours per day	16-20 hours	20-24 hours		
Capacity *	Up to 9000 passengers / hour		Up to 13500 passengers / hour	
Inclination	10°/11°/12°		0°-6°	
Pallet width [mm]	800 / 1000		1000 / 1200 / 1400	
Balustrade design	Vertical safety glass (10 mm safety tempered glass). Height 1000 mm			
Operating Speed [m/sec]	0.5			
Vertical rise [m]	2-8		0-8	
Max Installation Length [m]	-		120	
Motor type	One speed or VVVF			
Installation	Indoor, Semi-outdoor **, Outdoor			

^{*} Theoretical value based on calculations

^{**} Direct contact with rain or snow is not allowed for this Installation



